

DH-PW1

Application: Designed for pressure washer machines and equipment with working pressure up to 4000 PSI.

Tube: Black nitrile synthetic rubber

Cover: Cloth wrapped or smooth synthetic rubber cover (non marking)

Color: Black, Blue, Yellow, Grey and Red

Reinforcement: One high tensile steel wire braid

Temperature range: -40 °C to +100 °C

Part Number	Size	Max W.P.		Min B.P.		Min B.R.
	Inch	Mpa	Psi	Mpa	Psi	mm
DH-PW1-6	1/4	27.5	4000	82.5	12000	100
DH-PW1-8	5/16	27.5	4000	82.5	12000	115
DH-PW1-10	3/8	27.5	4000	82.5	12000	125
DH-PW1-13	1/2	20.5	3000	61.5	9000	180

DH-PW2

Application: Designed for pressure washer machines and equipment with working pressure up to 6000 PSI.

Tube: Black nitrile synthetic rubber

Cover: Cloth wrapped or smooth synthetic rubber cover (non marking)

Color: Black, Blue, Yellow, Grey and Red

Reinforcement: Two high tensile steel wire braid

Temperature range: -40 °C to +100 °C

Part Number	Size	Max W.P.		Min B.P.		Min B.R.
	Inch	Mpa	Psi	Mpa	Psi	mm
DH-PW2-6	1/4	41.5	6000	124.5	18000	100
DH-PW2-8	5/16	41.5	6000	124.5	18000	115
DH-PW2-10	3/8	41.5	6000	124.5	18000	130
DH-PW2-13	1/2	34.5	5000	103.5	15000	180

